




Specification

- Transparent ABS front cover permeable to light, water splashing proof, corrosion resisting, ageing resisting.
- Adopts patent heating technology- enclosed loop heating system with less heating loss.
- Multi-layer structure heating chamber form a long circulating water channel, no limescale, long lifespan.
- Electricity leakage protection, anti-scalding protection, over-pressure and over temperature protection. Water and electricity isolation protection.
- Direct temperature setting, automatically thermostat, the hot water temperature will be constant. Automatic memory function avoid repeated operation.
- LED widescreen touch display screen to show the working condition setting temperature and outlet temperature.
- Power consumption and water consumption display.
- Fault auto-detection technique, the cause will be displayed automatically while failure.

Technology Data

Model	XFJ50FTCH	XFJ60FTCH	XFJ70FTCH	XFJ100FTCH	XFJ120FTCH
Rated Voltage	220-240V				
Rated Power	5kW	6.5kW	7.5kW	9kW	11kW
Rated Current	21.7A	28.3A	32.7A	39.2A	47.9A
Rated Pressure	0.2-0.6MPa				
Efficiency M=25°C	2.92L/min	3.7L/min	4.3L/min	5.1L/min	6.3L/min
Safety Class	IP25				
Temp. setting range	30°C-55°C				
Overheat protection	67°C				
Connecting wires section	3*2.5mm ²	3*4mm ²	3*6mm ²	3*6mm ²	3*10mm ²
Thermal cut-off	90°C				
Pipe section	G1/2"				
Product Size	360*215*60mm				
Gift Box Size	420*125*280mm				
Carton Size (4pcs/CTN)	525*295*435mm				
Loading Quantity	20'GP: 1552pcs		40'GP: 3104pcs	40HQ: 3940pcs	




Multi point
Water Supply



Creepage
Protection




Over-pressure
Protection



Over temperature
Protection



Water and electricity
Isolation protection



Anti-scalding
Protection